



LAMA POLYFELT



QMS Certified Firm

For Roofing and Waterproofing

Description:

LAMA POLYFELT is non-woven polyester mat unsaturated or saturated with oxidized bitumen and faced on the upper side with fine granule and on the bottom side with polyethylene sheet to prevent sticking in the roll.

Uses:

- ❑ LAMA POLYFELT bitumen-saturated polyester is used in built-up roofing in layers bonded in bitumen conforming to ASTM D 1227 and ASTM D 2028-97.
- ❑ Also used as under lays for mopping asphalt conforming to ASTM D 449, B.S 3690: part 2, and ASTM D312, Type III & Type IV in roofing, flooring and retaining walls.

Technical Specifications

Property		Result
Roll dimension		1x20 m
Weight per roll		22 kg
Tensile Strength	Long.	130 N/5 em.
	Transv.	140 N/5 em.
Ultimate Elongation	Long.	25%
	Transv.	30%

- This Technical Data are the average results of tests, measurements and trials carried out by LAMA's own laboratory and RSS laboratories according to international standards such as ASTM, B.S and UEAtc.
- This product data sheet supersedes all previous data publications pertaining to this product.
- This data may be changed, improved or modified by LAMA, in accordance with the Client's requirements, availability of raw material, without advance notice.