



# E. Z. PATCH



QMS Certified Firm

## For the hole in the road – a quick remedy

### Introduction:

Repair it as soon as you can! For the hole will grow... causing more harm to traffic. E.Z. Patch is a quick remedy, an asphalt compound specially designed for instant repair of holes at path, roadway, and airport runways. E.Z. PATCH is a cold applied and simple to use. It allows repair to the site with minimum traffic disturbance.

### Application :

- Clean the hole and remove all loose materials, dust and moisture.
- It is advisable to prime the area with LAMAPRIMER, and allow it to be dry to touch.
- Fill the hole with E.Z. PATCH.
- Use a tamper or wet shovel to tamp the patch. Keep it little higher than the street level.
- The traffic will compact the patch. However, if heavy vehicles are expected, allow one day for the material to set to avoid dispersing.

### Standard:

E.Z. PATCH is composed of selected hard aggregates with asphalt binder that complies with the requirements of B.S. 3690, Grade 75/30.

### Containers:

E.Z. PATCH can be supplied in 25 kg plastic bags easy to use, carry and handle.

### Coverage:

E.Z. PATCH bag can repair one square meter area of 2.5 cm depth approximately.

- This Technical Data are the average results of tests, measurements and trials carried out by LAMA's own laboratory and RSS laboratories according to international standards such as ASTM, B.S and UEAtc.
- This product data sheet supersedes all previous data publications pertaining to this product.
- This data may be changed, improved or modified by LAMA, in accordance with the Client's requirements, availability of raw material, without advance notice.