



# LAMA FOGSEAL



QMS Certified Firm

## Emulsified Asphalt for Pavements

### Description:

LAMA FOGSEAL is cold applied emulsified asphalt for the application on pavements before applying the asphalt paving layer.

### Application :

- Before application dilute LAMA FOGSEAL with water, one to one.
- Apply only when existing surface is dry and there is no threat of rain. Apply when atmospheric temperature is above 10°C.
- Following the preparation of the surface, apply the water diluted asphalt emulsion at a rate that will not leave an excess on the surface.
- Maintain application temperature of emulsified asphalt between 24 and 71°C.
- Treat spots unavoidably missed with the hand spray equipment.

### Protection and Precautions:

During applications, protect adjacent buildings, structures, vehicles, manhole covers, inlet grates and trees to prevent being spattered or marred. Keep all traffic off freshly treated surfaces for at least 2 hours. Provide warning signs and barricades for proper traffic control.

### Containers:

LAMA FOGSEAL can be supplied in 200 Liters drum.

### Coverage:

LAMA FOGSEAL shall be uniformly distributed at rates of 1 to 2 liters per square meter according to the type of surface.

### Surface Preparation:

- Clean the surface to receive the LAMA FOGSEAL.
- Remove dirt, clay, vegetation, loose and flaking paint, or other objectionable material by means of power brooms, power blower or other approved equipment.
- When necessary to achieve a clean surface, flushing with water will be permitted.

### Flammability

Non-combustible, non-flammable.

### Standard:

LAMA FOGSEAL complies with the requirements of ASTM D977- 98.

- This Technical Data are the average results of tests, measurements and trials carried out by LAMA's own laboratory and RSS laboratories according to international standards such as ASTM, B.S and UEAtc.
- This product data sheet supersedes all previous data publications pertaining to this product.
- This data may be changed, improved or modified by LAMA, in accordance with the Client's requirements, availability of raw material, without advance notice.