



# LAMA Asphalt Glue



QMS Certified Firm

## For road markers

### Description:

LAMA ASPHALT GLUE is a blend of adhesive and high melting point bitumen, with graded mineral filler. It is hot poured to fix tenaciously road markers to Portland cement and asphaltic concrete roads.

### Application:

- ❑ Heat the Glue in a melter with continuous agitation to 160-180°C. Pouring temperature is 160 - 170°C.
- ❑ Fill the predrilled hole with the hot Glue, and place the marker into the puddle immediately.

**Note:** The pavement must be dry and free from loose concrete or dirt. Do not install in cold weather.

### Containers:

LAMA ASPHALT GLUE can be supplied in 20Kg blocks wrapped in polyethylene film, suitable for easy depositing into the melter.

### Technical Specifications

| Property                         | Result | Standard |
|----------------------------------|--------|----------|
| Penetration at 25°C, 40 dmm max. | 40 dmm | ASTM D5  |
| Softening point, min.            | 110 °C | ASTM D36 |
| Specific gravity                 | 1.5    |          |
| Bitumen content, min.            | 55 %   |          |
| Filler content, max.             | 45%    |          |
| Flash point, min.                | 220 °C |          |

- This Technical Data are the average results of tests, measurements and trials carried out by LAMA's own laboratory and RSS laboratories according to international standards such as ASTM, B.S and UEAtc.
- This product data sheet supersedes all previous data publications pertaining to this product.
- This data may be changed, improved or modified by LAMA, in accordance with the Client's requirements, availability of raw material, without advance notice.